



Televes reserves the right to modify the product

Ultra-compact Splitting Terminal Enclosure Up to 12 fibres

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure). Its ultra-compact and discreet design makes it easy to install without disturbing the aesthetics of the site.

Can house up to 12 fibres.

Ref.231304

Art.Nr	OVB12UK
EAN13	8424450266878

Highlights

- Ultra-compact and discreet format
- Possibility to increase capacity up to 24 fibres with the extension frame (Ref. 231305)
- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring through the side openings
- Security: screw fastening, to avoid external manipulation
- Grey colour (RAL 7035)
- Equipped with 1 trays, for up to 12 heat-shrink splices, vertically stacked, over the 6 positions it has
- Includes stows for different splices
- Screws for wall mounting are included
- Ingress protection code IP30 and impact protection code IK10
- Dimensions (W x H x D): 136mm x 136mm x 45mm

Technical specifications

Number of fibers		12
Pre-cut openings		No
Independent compartments		No
Closure type		Cover
Front door locking system		Screw
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		30
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Colour		Grey
Height	mm	136
Width	mm	136
Depth	mm	45