



Optical fiber patch cord SC/APC – FC/UPC, Single-mode (SM), LSFH indoor

Single-mode (SM) optical fiber patch cord, Pre-terminated on one end with an SC/APC connector and with an FC/UPC connector on the other; it can thus be used as an adapter for devices with different connectorization. The sheath being LSFH, it is recommended for indoor use.

Ref.	232624
Logical ref.	OSK2SCFC
EAN13	8424450208717

Other features

Colour	Orange
Length	2.00 m

Packaging info

Bag	1 pcs.
Box	10 pcs.

Physical data

Net weight	24.00 g
Gross weight	24.00 g
Width	3.00 mm
Height	2,000.00 mm
Depth	3.00 mm
Main product weight	24.00 g

Highlights

- LSFH sheath, orange colour
- SC/APC and FC/UPC connectors

- 2m long

Technical specifications : Ref. 232624

Fiber core type		Single-mode (ITU-T-G.657.A2)
Optical fiber type category		OS1
Fiber core diameter	µm	9
Fiber cladding diameter	µm	125
Coating buffer diameter	µm	250
Cable structure		Tight buffer
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0.4
Attenuation 1490nm	dB/km	< 0.4
Attenuation 1550nm	dB/km	< 0.3
Insertion losses in connector 2	dB	< 0.5
Return losses in connector 2	dB	> 60
Optical connector type 1		FC
Polishing type (Optical connector 1)		UPC
Optical connector type 2		SC
Polishing type (Optical connector 2)		APC
Cable length	m	2
Minimum bending radius	mm	15
Operating temperature	°C	-20 ... 70