



Televes reserves the right to modify the product

OPS3L Triple light source 3 wavelengths: 1310nm, 1490nm, and 1550nm

Three-wavelength generator (1310 nm, 1490 nm, 1550 nm) to measure the optical attenuation of an installation.

Ref.2340

Art.Nr

OSG3WL

EAN13

8424450146002

Highlights

- Ergonomic, light-weight and robust
- LCD display
- Operation and keyboard LED

Main features

- Compatible with FC, SC, and ST APC connectors thanks to the integrated adapters
- 12V power supply
- Equipped with a 1-m FC/APC SC/APC patch cord
- Equipped with a 1-m FC/APC FC/APC patch cord
- Cleaning buds included

Technical specifications

General			
Display			LCD 128 x 64 px
Generated wavelength		nm	1310, 1490, 1550
Modulation		Hz	270, 1K, 2K
Tolerance		nm	± 20
Laser			Fabry Péro
Output power		dBm	-8 ... 0 (1dBm steps)
Precision		dBm	0.25 (25°C ±3°)
Output connector			Adapter SC, FC and ST (APC)
Stability	Short-term (15min)	dB	< ±0,1
	Long-term (2h)	dB	< ±0,3
External units and batteries			
Battery			Li-Ion 7.4 V
External power supply		V	12
Max. consumption		W	12
Autonomy			26 hours