



Televes reserves the right to modify the product

T12 single-channel/multi-channel amplifier UHF (DTT): 470...862 MHz

Modular amplifier allowing the adjustment of individual UHF channels (DTT). Each module allows the amplification of 7 consecutive channels (to be specified with the module's order). Perfect format for headend mounting, with additional T12-series amplifiers.

RED compliant

Ref.508612

Art.Nr

T12UHF55

EAN13

8424450239599

Highlights

- Modular system that eases extension, custom configuration, and amplifier replacement
- Very high gain (adjustable)

Main features

- Mounting on DIN rail, case or rack
- Provided with all the elements required for commissioning (jumpers, power supply patch cords, etc.)

Discover

T12 series: Single-channel amplification

The evolution of single-channel amplification results in the advanced T12 product line.

This series brings together the experience gained by Televes ever since the introduction of its first single-channel module with Z connection system in the market, back in 1981. The result is an end product that provides an unbeatable

performance in terms of signal processing, with precise and simple frequency settings.

T.12 modules are manufactured in new generation automated lines, and undergo the most stringent quality controls, a guarantee of unprecedented reliability and stability. Designed for adaptation, the T12 series is always the most flexible solution for the relocations entailed by the digital dividend: a product with the LTE-Ready seal.

T12 series features

- Full compatibility with the previous T03 model and its power supply
- Highly reliable, thanks to its fully automated manufacturing
- Significant enhancement of the shielding design, with a Zamak chassis
- Power supply of up to 24 modules, thanks to a power supply the size of one module
- Remote powering of pre-amplifiers or BOSS system by means of a switch

Technical specifications

Frequency margin		MHz		470...890
Bandwidth	MHz	CCIR		8±56
		NTSC		6±48
Gain		dB		50
Gain regulation				30
AGC dynamic margin				-
Equalizer				-
Max.output level	dBµV	A EN 50083-5		125±111
		D EN 50083-5		118±102
	dBmV	A EN 50083-5		65±51
		D EN 50083-5		58±42
Max. current input		mA		100
Power supply		Vdc		24
Current consumpt		mA		95
Flatness		dB		<3
Rejection	CCIR	dB	Rn±1	>3
			Rn±2	>25
			Rn±3	>45
	NTSC		Rn±1	-
			Rn±2	>20
			Rn±3	>40
Protection Level		IP		20