



Multimedia end outlet 3 connectors: FM-TV-DATA

End outlet equipped with three connectors. The IEC male connector for terrestrial TV is located on the lower left side, while the IEC female connector for FM (radio) is located on the lower right side; an F connector for multimedia data is located at the top centre.

Specifically designed for operators, DOCSIS 3.1 compatible.

Ref.	524001
Logical ref.	KME04ST
EAN13	8424450135754

Packaging info

Box	1 pcs.
Carton	10 pcs.
Carton	100 pcs.

Physical data

Net weight	94.00 g
Gross weight	94.00 g
Width	70.00 mm
Height	67.00 mm
Depth	36.00 mm
Main product weight	94.00 g

Highlights

- Robot-controlled automated manufacturing
- High shielding
- Outstanding isolation between outputs

- Made of Zamak, high strength
- Compatible with coaxial cable with sheath diameters in the 5-to-6,9 mm range (Ø 5...6,9 mm)

Discover

Televes outlets: Screw-free mounting

A class A outlet offering numerous advantages:

- The inner conductor is connected simply by pushing, without the need for screws; still the gripping force is equivalent
- Supports inner conductor diameters from 0.65 mm to 1.2 mm, and external cable diameters from 5 mm to 6.9 mm
- F-connector type conic guide for easy inner conductor introduction
- Wide margin in inner conductor length (from 5 mm to 15 mm), which makes short circuits between core and mesh difficult
- Tilt-up, self-supporting, full-opening clamp
- The clamp is equipped with 3 jagged rows in 9 mm for a perfect braid fixing
- Printed circuit board perforation to make the faceplate fixing screw compatible
- Rounded edges to prevent cuts
- Class A shielding

Furthermore, this product range includes several engravings on the chassis:

- CE marking
- Numerical and logical references
- Input and output indications
- Cable stripping dimensions

Technical specifications : Ref. 524001

Fastening method			Without screws		
Number of connectors			3		
R Connector			"IEC" female		
TV Connector			"IEC" male		
DATA Connector			"F" female		
Pass-through output			No		
Bands		FM	TV	DATA	
Frequency range	MHz	87 ... 1218	111 ... 1218	5 ... 1218	
Rejection between outputs	dB	> 30	> 30	> 30	
Attenuation: R Connector	dB	7	--	--	
Attenuation: TV Connector	dB	--	8	--	
Attenuation: DATA Connector	dB	--	--	3.6	
DC pass			SATIn		
Max. current	mA		350		