



Televes reserves the right to modify the product

NevoSwitch equipped with 5 QUAD inputs and 6 outputs

When quality matters

Cascadable and quad-compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 6 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.714402

Art.Nr

MS56NCQ

EAN13

8424450172858

Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications

Technical specif.			
Type			5x5x6 QUAD
Frequency range	MHz	SAT	950 ... 2200 / 2400
		TERR	47 ... 862
Input level	dB μ V	SAT	105
		TERR	92
Through losses	dB	SAT	1.5 ... 3 / 4
		TERR	2
Tap losses. 1..8 / 9..16 / 17..24 / 25..32	dB	SAT	1(1) / - / - / -
		TERR	2 / - / - / -
Isolation	dB	H/V	>30
		Users	>25
DC pass			In-Out / Out-In
Max. total consump	mA	PSU (3)	40
		SAT STB(4)	35
Temp. range.	°C		-5 ... +45 °C
Protection level	IP		IP20

(1) Gain

(3) if output charged => + 25mA

(4) 35 mA + PSU POWER if not external PSU