



Televes reserves the right to modify the product

NevoSwitch 17 inputs - 32 outputs

When quality matters

Multiswitch equipped with 17 inputs (one terrestrial and 16 for four satellites, each with its four polarities) and 32 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.714805

Art.Nr

MS1732C

EAN13

8424450173275

Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades
- Compatible with return-channel applications
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications

Technical specif.				
Type			17x17x32	
Frequency range	MHz	SAT	950 ... 2200 / 2400	
		RF	88 ... 862	
		RP	5 ... 65	
Input level	dBμV	SAT	112	
		RF	90	
Through losses	dB	SAT	8 ... 13.5 / 18	
		RF	8	
		RP	12	
Tap losses 1..8 / 9..16 / 17..24 / 25..32	dB	SAT (1)	3/6/10/14	
		RF	4 / 6 / 8 / 10	
		RP	34 / 37 / 40 / 43	
Isolation	dB	H/V	>30	
		Users	>25	
DC pass			In-Out / Out-In	
Max. total consumption	mA	PSU	Low Gain(2)	170
			High Gain(2)	350
		Receiver	40	
Temp. range	°C		-5 ... +45 °C	
Protection level	IP		IP20	

(1) LG - 10 dB

(2) if output charged => + 85mA