



Televes reserves the right to modify the product

NevoSwitch tap

5 inputs 12dB

NevoSwitch tap equipped with 5 inputs (one terrestrial and the four polarities of one satellite), with 12 dB bridging losses, that allows the balancing of the signals received by each user.

Ref.714901

Art.Nr

AZS512G

EAN13

8424450173404

Highlights

- Current circulation in all inputs and all outputs with DC bypass
- Current circulation in the vertical low (VL) bypass and terrestrial output
- Low through losses

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Passive element that does not require power feeding

Technical specifications

Technical specifications			
Type			5x5x5
Frequency range	MHz	SAT	950 ... 2400
		TERR	47 ... 862
Input level	dB μ V	SAT	-
		TERR	-
Through losses	dB	SAT	1,5 \pm 0,5
		TERR	1,5 \pm 0,5
Tap losses 1..8 / 9..16 / 17..24 / 25..32	dB	SAT	15 \pm 3
		TERR	12 \pm 1
Isolation	dB	H/V	>25
		Users	>25
DC Pass			-
Max. total consump.	mA	PSU	-
		SAT STB	-
Temp. range	°C		-5 ... +45 °C
Protection level	IP		IP20