



Televes reserves the right to modify the product

SMATV optical receiver without Return Path 1200...1600 nm

They receive an optical signal in the 1200 nm-1600 nm range to restore the original RF signal transformed by a transmitter. The RF band is compatible with SMATV (87 MHz - 2400 MHz). Perfect for RFoG / RF Overlay solutions.

Ref.2335

Art.Nr

UOE1216

EAN13

8424450147603

Highlights

- Wide reception optical range
- Output level above 90 dBμV
- Optical power LED indicators
- The output band includes SAT, up to 2400 MHz
- Optical power drop alarm

Main features

- Perfect for RF overlay solutions
- Very low equivalent noise conversion
- Adjustable attenuator
- Easy to install and use
- High energy efficiency
- SC/APC optical connectors, and F-type connectors for RF

Technical specifications

RF Input/Output	Frequency range		Forward channel	MHz	87 - 2400
			Return channel		----
	Maximum Output Level for CSO and CTB >= 60dB		87-862 MHz	dBµV	93
			950-2400 MHz		90
	Output level regulation margin (in 2 dB steps)			dB	0 - 18
	Maximum input level return path			dBµV	----
	Equivalent input noise of the return channel, measured at 30 MHz and the transmitter output connected directly to the receiver			dBm/Hz	-152,5
	Flatness			dB	± 1,5
	Return losses			dB	>= 11
Impedance			ohm	75	
Optical input (forward channel)	Optical device			type	InGaAs Pin Photodiode
	Wavelength			nm	1200 -1600
	Detection bandwidth			MHz	1 - 3000
	Maximum Optical power received			mW/dBm	4 / 6
Optical output (return channel)	Laser			type	----
	Wavelength			nm	----
	Maximum output power			mW/dBm	----
General	Powering/Consumption		12 Vdc	mA	300
			24 Vdc		155
	RF connectors			type	F hembra
	Optical connectors				SC/APC
	Operating temperature			°C	-5 ... +45