Televes



Televes reserves the right to modify the product

DTKom broadband multiband amplifier 5 inputs: FM-BIII-21..36-38..48-UHF -LTE700 Ready

High-power multiband amplifier with multiple controls on the front end, which design uses components that minimize the total noise figure. Equipped with 5 inputs (FM-BIII-21...36-38...48-UHF). The UHF band is divided in 2 of the inputs, which is useful in two-repeater reception installations since it allows an appropriate filtering of the channels for each of them.

Equipped with LTE700 filtering. **RED** compliant

Ref.534120

Art.Nr

EAN13

8424450214558

Highlights

- Separate amplification minimizes intermodulation between bands and provides high output levels
- Designed using Push-Pull technology, which guarantees levels in the 123 dBµV range for terrestrial signals.
- Includes a high-performance low-power consumption switch-mode power supply
- High-screening Zamak chassis The design facilitates appropriate cooling

Main features

- Switch for pre-amplifier or BOSS system powering
- Switched configurable gain (high/low), and high output level
- Intuitive front cover, including adjustments and block diagram
- Output signal LED indicator

Televes®

Technical specifications

Bands			UHF	BV	BIV	BIII	FM
Frequency margin		MHz	470 694	606 694 (Ch3848)	470 598 (Ch2136)	174 370	88 108
Gain	0	dB	42	41 ⁽¹⁾	41 ⁽²⁾	42	25
	10		32	31 ⁽¹⁾	31 ⁽²⁾	32	25
Gain margin			(Manual) 0 20	(Manual) 0 20	(Manual) 0 20	(Manual) 0 20	(Manual) 0 20
Max. output level	IMD3 (2 tones,-35 dB)	dBµV (dBmV)	125 (65)				
	DIN 45004B		123 (63)				
	IMD3 (2 tones,-60 dB)		120 (60)				
	IMD2 (2 tones,-60 dB)		-	-	-	122 (62)	-
Noise figure		dB	10	10	10	5	6
Test			-20				
Powering inputs		V=	12				
Max. curent inputs		mA	50				
Mains voltage /frequency		V~ / Hz	120 230 / 50-60				
Total AC consumption	OFF	W/mA	5,8 / 120				
	ON	W/mA	9,6 / 180				
Protection level		IP	20				
Operating temperature range		°C (°F)	-5 +45 (23 113)				

⁽¹⁾ G(Ch38)=37/27dB

⁽²⁾ G(Ch36)=38/28dB