Televes°



Televes reserves the right to modify the product

NevoSwitch 17 inputs - 8 outputs

When quality matters

Multiswitch equipped with 17 inputs (one terrestrial and 16 for four satellites, each with its four polarities) and 8 user outputs. Can be used as a terminal (star topology) or as a cascade by using a simple switch.

Ref.714801

Art.Nr MS178C

EAN13 8424450173237

Highlights

- 10 dB Low Gain (LG) / High Gain (HG) switch for the attenuation of the satellite input signal for each 8-user group
- Remote power feeding using VL
- Current circulation between all inputs and cascades
- Compatible with return-channel applications
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Televes®

Technical specifications

Number of inputs		17
Number of cascadable outputs		17
Number of user outputs		8
Frequency range TERR.	MHz	88 862
Frequency range SAT.	MHz	950 2400
Input level TERR.	dΒμV	90
Input level SAT.	dΒμV	112
Through losses TERR.	dB	2
Through losses SAT.	dB	2 5
Tap losses 18 TERR.	dB	4
Tap losses 18 SAT.	dB	3
Isolation H/V	dB	> 30
Isolation users	dB	> 25
Powering	Vdc	12
Max. current (PSU - LG)	mA	45
Max. current (PSU - HG)	mA	90
Max. current (STB)	mA	40
Operating temperature	°C	-5 45
Protection index		20