

NevoSwitch equipped with 5 QUAD inputs and 8 outputs

Televes

When quality matters

Cascadable and quad-compatible multiswitch, equipped with 5 inputs (one terrestrial, and the four polarities of one satellite) and 8 user outputs.

Can be used as a terminal (star topology) or as a cascade by using a simple switch.

| | |
|-------------------|--------------------------|
| Ref.714413 | 12 V and 1.5 A (UK plug) |
| Art.Nr | MSUK58NCQ |
| EAN13 | 8424450177891 |

Highlights

- 12 V power supply (ref. 9916) included
- A 22 kHz tone can be generated, which makes it compatible with any LNB, including QUAD LNB.
- A switch for either powering terrestrial pre-amplifiers or allowing current circulation
- Remote power feeding using VL
- DC circulation from the inputs up
- Active terrestrial
- European design, quality, and manufacturing

Main features

- Very compact
- Made of zamak
- Input and output colour identification
- Available ECO mode
- Selector switch to shift between cascade and terminal modes
- 12 V power supply
- Low power consumption

Technical specifications

| Technical specif. | | | |
|---|------------|------------|---------------------|
| Type | | | 5x5x8 QUAD |
| Frequency range | MHz | SAT | 950 ... 2200 / 2400 |
| | | TERR | 47 ... 862 |
| Input level | dB μ V | SAT | 105 |
| | | TERR | 92 |
| Through losses | dB | SAT | 1.5 ... 3 / 4 |
| | | TERR | 2 |
| Tap losses. 1..8 / 9..16 / 17..24 / 25..32 | dB | SAT | 1(1) / - / - / - |
| | | TERR | 2 / - / - / - |
| Isolation | dB | H/V | >30 |
| | | Users | >25 |
| DC pass | | | In-Out / Out-In |
| Max. total consump | mA | PSU (3) | 40 |
| | | SAT STB(4) | 35 |
| Temp. range. | °C | | -5 ... +45 °C |
| Protection level | IP | | IP20 |

(1) Gain

(3) if output charged => + 25mA

(4) 35 mA + PSU POWER if not external PSU