



*Televes reserves the right to modify the product*

## Splitting Terminal Enclosure Up to 16 fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Can house up to 16 splices.

**Ref.231301**

**Art.Nr**

OVB8

**EAN13**

8424450153222

### Highlights

- Built in high-resistance ABS
- Multi-fiber cable input/output of the main wiring system made by cones designed to house different fiber diameters
- Security: Door with lock, to avoid external manipulation
- Grey colour (RAL 7035)
- Equipped with 2 independent removable trays, for up to 8 splices each
- Equipped with 2 stuffing gland at the bottom for optical fiber output. Each stuffing gland can house 4 cables of two 2 fibers each
- Includes 2 sets of stows for different splices (the first one supports 12 splices, the second 16)
- Screws for wall mounting are included
- Ingress protection code IP43 and impact protection code IK10
- Dimensions (W x H x D): 163mm x 265mm x 69mm

## Technical specifications

Number of fibers		16
Pre-cut openings		No
Independent compartments		No
Closure type		Door
Front door locking system		Key Lock, one-point lock
Type of connections		Fusion splice
Installation type		Wall
Protection index (IP)		43
Protection index (IK)		10
Grounding		No
Material		ABS Plastic
Color		Grey
Height	in	10.433
Width	in	6.417
Depth	in	2.717