



Televes reserves the right to modify the product

Splitting Terminal Enclosure Up to 48 fibers

Designed to work as a pass-through and diverting element for optical fiber cables, it can handle up to 48 splices on 4 trays. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

Its large dimensions make installer's work easier when it comes to merging, splitting and placing the different fibers.

Ref.231302

Art.Nr

OVB24

EAN13

8424450181799

Highlights

- Built in high-resistance ABS
- Fully configurable fiber inputs and outputs
- Fully separable, to facilitate the optical fibers installation/segregation procedure
- Easy to work on, with multiple anchors and fiber guides
- Security: Door with lock, to avoid external manipulation
- Grey colour (RAL 7035)
- Equipped with 8 rubber fiber guides, 4 trays and 8 splice stow supports
- All the accessories required for fiber cable support and wall anchoring are provided
- Ingress protection code IP30 and impact protection code IK10
- Dimensions (W x H x D): 208mm x 291mm x 110mm

Technical specifications

| | | |
|---------------------------|----|--------------------------|
| Number of fibers | | 48 |
| Pre-cut openings | | Yes |
| Independent compartments | | No |
| Closure type | | Cover |
| Front door locking system | | Key Lock, one-point lock |
| Type of connections | | Fusion splice |
| Installation type | | Wall |
| Protection index (IP) | | 30 |
| Protection index (IK) | | 10 |
| Grounding | | No |
| Material | | ABS Plastic |
| Color | | Grey |
| Height | in | 11.811 |
| Width | in | 8.11 |
| Depth | in | 4.331 |