



Televes reserves the right to modify the product

Optical fiber patch cord LC/UPC, Single-mode (SM), LSFH indoor

Single-mode (SM) optical-fiber patch cord pre-terminated with LC/UPC connectors for the interconnection of optical equipment. The sheath being LSFH, it is recommended for indoor use. Supplied in individual packing.

Ref.232672

Art.Nr

OSK2LCUPC

EAN13

8424450240922

Highlights

- Low attenuation
- Includes aramid fibers to reinforce its structure
- ITU-T G.657.A2 fiber type
- LSFH sheath, orange colour
- LC/UPC connectors
- 2m long

Technical specifications

Fiber core type		Single-mode (ITU-T-G.657A2)
Optical fiber type category		OS1
Fiber core diameter	μm	9
Fiber cladding diameter	μm	125
Coating buffer diameter	μm	250
Cable structure		Tight buffer
Plastic buffer diameter	mm	0.85
Outer sheath Diameter	mm	3
Outer sheath Material		LSFH
Blocking jelly		No
Attenuation 1310nm	dB/km	< 0.4
Attenuation 1550nm	dB/km	< 0.3
Insertion losses in connector 1	dB	< 0.5
Insertion losses in connector 2	dB	< 0.5
Return losses in connector 1	dB	> 50
Return losses in connector 2	dB	> 50
Optical connector type 1		LC
Polishing type (Optical connector 1)		UPC
Optical connector type 2		LC
Polishing type (Optical connector 2)		UPC
Short tension	N	450
Long tension	N	200
Structure reinforcement element		Aramid fibers
Short crush (@100mm)	N	500
Long crush (@100mm)	N	100
Minimum bending radius	mm	15

Operating temperature	°C	-20 ... 70
-----------------------	----	------------