



| OPERATION | API | EXTENDED API <i>Option 593212</i> |
|----------------------|-----|--------------------------------------|
| REMOTE CONFIGURATION | ● | ● |
| CHANNEL MEASURES | ● | ● |
| SCAN | | ● |
| TILT | | ● |
| SPECTRUM | | ● |
| LEARNING PLAN | | ● |
| BANDWIDTH | | ● |
| AUDIO | | ● |
| FREQUENCY | | ● |
| TUNING | | ● |
| AUTO SUSPEND | | ● |
| AUTO POWER OFF | | ● |

Televes reserves the right to modify the product

Option Advanced API for H30+ & H30D+ meters

This option, which can be installed on the H30+ & H30D+, allows the remote configuration* of the devices according to the user's needs. Among the meter parameters that can be configured with this functionality, we can find:

- Language
- Network connection (wired or wireless)
- Units (dBuV, dBmV or dBm)
- Channel selection (within a pre-established channel plan)
- Channel frequency
- Plan selection (within the plans contained in the equipment)
- Channel identification (automatic or manual)
- Tuning (by channel or by frequency)
- Quality profile
- Bandwidth
- Audio level
- Spectrum span
- Spectrum reference level (automatic or manual)
- Scan type
- Input frequencies
- Input reference level (automatic or manual)
- Tilt features
- Auto suspend
- Auto power off

(*) To use of this option, the equipment must be connected to the network.

Ref.593212

| | |
|--------|---------------|
| Art.Nr | H30API |
| EAN13 | 8424450177334 |

Highlights

- Compatible with the H30+ & H30D+ field strength meters

