Televes®



Televes reserves the right to modify the product

ONU Basic module 1x GbE Ethernet

The Optical Network Unit (ONU) is a customer premises equipment (CPE) in charge of delivering the services at the subscriber's home. The Basic type provides 1 GbE Ethernet port.

Ref.769507			
	Art.Nr	ONTB	
	EAN13	8424450183809	

Highlights

• Remote configuration without subscriber intervention

Discover

What is a ONT/ONU?

The Optical Network Terminal (ONT) or Optical Network Unit (ONU) is the device in charge of delivering the services the user contracted from the operator. The terminal range conforms to installation and implemented services criteria. ONT can be used in the network topologies known as FTTx: Fiber-to-the-Home (FTTH), Fiber-to-the-Room (FTTR), Fiber-to-the-Building (FTTB), Fiber-to-the-Business (FTTb), Fiber-to-the-Curb (FTTC), etc.

Multiple-play signals provisioned at the FibreData headend, such as High Speed Internet (HSI - High Speed Internet), VoIP, WiFi, IPTV and/or RF Overlay, etc., are available in their connectors.

How to select an ONT/ONU?

Based on the considered connection interface, several options are available in the whole range of network optical equipment. A comparison of the features each of them provides is described below.

Reference 769514	769507
------------------	--------

Televes®

Models	ONT	ONU	
Models	HOSPITALITY WIFI AC	BASIC	
RF-Overlay	✓	-	
WiFi (802.11 b/g/n) (3x3) 2.4	~	-	
WiFi (802.11 b/g/n/ac) (4x4) 2.4/5	·	-	
USB	1	-	
FXS Ports	2	-	
ETH 10/100/1000BASE-T Ports	4	1	
Maximum number of WAN Services supported by ONT	7	-	
NAT/NAPT	✓	-	
Firewall	✓	-	
/PN pass-through	~	-	
PPPoE terminal	~	-	
OMCI	~	-	
TR-069	~	-	
CLI	~	-	
WebGUI	✓	-	

Televes®

Technical specifications

Optical Network Unit type		ONU BASIC
Number of Gigabit Ethernet ports (10/100/1000BaseT)		1
Powering	Vdc	12
Max. current	mA	1
Max. power consumption	W	12
Operating temperature	°F	23 122
Relative humidity	%	0 95