



Televes reserves the right to modify the product

SMATV optical transmitter, 1RU rack 19" 1310 nm, Po 6 dBm

Produces an optical signal in the 1310 nm-window modulated by the input RF SMATV signal (47 MHz- 2400 MHz). The optical output power is 6 dBm.

Perfect for RFoG / RF Overlay solutions.

Ref.769902

Art.Nr

U19OS136

EAN13

8424450197745

Highlights

- SMATV-compatible: up to 2400 MHz input bandwidth
- RF input level control: optimization of the optical conversion quality parameters
- Optical power drop alarm
- 19"-rack installation, 1U height

Main features

- Very low equivalent noise conversion
- Easy to install and use
- High energy efficiency
- SC/APC optical connectors, and F-type connectors for RF

Technical specifications

RF parameters	RF frequency range	MHz	47 ... 2400
	RF input level (AGC: ON)	dBµV/dBmV	75...90 / 15...30
	SAT input level (AGC: ON)	dBµV/dBmV	RF - 10dB
	RF manual gain adjust	dB	0 ... 14 (steps 2 dB)
	CAG control	dB	20
	Flatness (47...1220MHz)	dB	± 0,5
	Flatness (950...2400MHz)	dB	± 2
	Return losses (47...1220MHz)	dB	≥ 10
	Return losses (950...2400MHz)	dB	≥ 7
	Impedance	Ohm	75
	CSO (CENELEC 42)	dB	≥ 60
	CTB (CENELEC 42)	dB	≥ 60
	C/N	dB	>50
Optical	Laser	type	MQW-DFB
	Wavelength	nm	1310 ± 10
	Optical power	dBm	6
General	RF connectors	type	F female
	Optical connectors		SC/APC
	Supply voltage	VAC	110 - 230
	Frequency	Hz	50/60
	Power consumption	mA	100
	Operation temperature	°C / °F	-5.....45 / 32.....113