



6 mm-diameter steel cable (Ø 6 mm) Galvanized

6 mm-diameter (Ø 6 mm) galvanized steel cable made of 7 wires, each with a diameter of 2 mm (Ø 2 mm).

They allow the fixing of mechanical fixtures such as towers and masts, usually by means of guy wires. Supplied in 200 m rolls.

| | |
|---------------------|---------------|
| Ref. | 306001 |
| Logical ref. | TDS6 |
| EAN13 | 8424450168530 |

Packaging info

| | |
|-------------|-------|
| Reel | 200 m |
|-------------|-------|

Physical data

| | |
|----------------------------|-------------|
| Net weight | 190.00 g |
| Gross weight | 190.00 g |
| Width | 6.00 mm |
| Height | 1,000.00 mm |
| Depth | 6.00 mm |
| Main product weight | 200.00 g |

Highlights

- Breaking strain above 3000 Kp (29,500 N)

Technical specifications : Ref. 306001

| | | |
|-----------------------|-----|------------|
| Transversal section | mm² | 28.274 |
| Nominal diameter | mm | 6 |
| No. interleaved wires | | 7 |
| Wire diameter | mm | 2 |
| Material | | Steel |
| Surface protection | | Galvanized |
| Breaking load | N | 29500 |
| Colour | | Grey |